

915 2-wire Video Doorphone

of Building System

Designed and produced in Taiwan



915C7 PH-NP
stainless steel camera
name plate



915C3AL
aluminum door
bell with CCD



915C5
aluminum
button camera



915K2
20-key button



915C8/C8M
stainless steel camera
/stainless steel camera
with mifare card reader



915M7
7" color LCD Monitor



915M35
3.5" color LCD Monitor



915M7b - white

7" Touch Pad Handsfree video monitor



915M7b - black



915Mi
4" color LCD Monitor



915Mh
4" color LCD Monitor



915M3
Audio Handset



915Mg
Audio Handsfree



915P
power supply



915SP
splitter



915SX
switching box for door bell



915CSb
Camera Selector

915 2-wire Video Doorphone of Building System

Specifications and Features as below :

1. 2-wire digital video doorphone system, Power / Color video / Two-way handsfree communication / Door release / Door status Indicator/ Monitoring / Calling all these functions are through 2-wire system. (A realize 2 lines (power line free))
2. System basic framework: Main entrance camera(max. capacity is 4 cameras) / Control center/ Door bell camera(for apartment door, max.capacity is 4 cameras)/ Main monitor / Sub-monitor/ Audio handset.
3. There are 2 kinds of main cameras for choosing - digital and key pad type. SUS304 stainless steel or aluminum front panel, strong structure and elegant appearance.
4. Main camera / Door bell camera with built-in ir LED , the ccd will automatically change to black-white picture and ir LED light on when the dark night is coming , let you see the visitor easily .
5. Main camera with built-in contact for connecting door lock. Door status indicator can let tenant to know whether the door of main camera is close or not. The open door time can be adjusted from 2 sec. to 15 sec. depends upon tenant's requirement.
6. LCD wide visual angle LED TFT monitor, follow the trend of energy saving & carbon reduction ,support green energy development .
7. Sometimes the installation environment has not a good sound insulation.You can connect an external loudspeaker to main monitor for easing to know visitors.
9. Main monitor can support picture output to DVR/CCTV Monitor.

915 2-wire Video Doorphone

For Villa Type

Designed and produced in **Taiwan**



915C10AL

1-key/2-key aluminum camera



915M7b - white



915M7b - black

7" Touch Pad Handsfree video monitor



915C11

color ABS camera




915C10AL

1-key color aluminum camera

PH-915C3ALM

1-key color aluminum camera with Mifare card reader

2-wire only



Cat5e



915M7

7" LCD

handsfree monitor



915M35

3.5" LCD


handsfree monitor



915Mi

4" LCD

handsfree monitor



915Mh

4" LCD

handsfree monitor

915 2-wire Video Doorphone for villa type :

Specifications and Features as below :

1. 2-wire digital video doorphone system, Power / Color video / Two-way handsfree communication / Door release / Door status Indicator/ Monitoring / Calling all these functions are through 2-wire system. (A realize 2 lines (power line free))
2. System basic framework:
Camera(max. capacity is 4 cameras)
Monitor(max. capacity is 6 monitors)
3. There are 2 kinds of cameras for choosing - ABS Camera and Aluminum Camera .
Strong structure and elegant appearance.
4. Camera with built-in IR LED , the CCD will automatically change to black-white picture and IR LED light on when the dark night is coming , let you see the visitor easily .
5. Camera with built-in contact for connecting door lock.
Door status indicator let tenant to know whether the door is close or not. The open door time can be adjusted from 2 sec. ~ 15 sec. depends upon tenant's requirement.
6. LCD wide visual angle LED TFT monitor, follow the trend of energy saving & carbon reduction ,support green energy development .
7. Sometimes the installation environment has not a good sound insulation.You can connect an external loudspeaker to main monitor for easing to know visitors.
9. Main monitor can support picture output to DVR/CCTV Monitor.



915P

Switch power for 2-wire system



915CSb

Camera Selector

KANRICH[®]

